

FEATURES



- High Resolution 5" TFT LCD Monitor
- Free Input Voltage (DC 10V ~ 30V)
- NTSC/PAL Compatibility
- 2 Camera Inputs (4-pin mini DIN)
- Low Reflection TFT LCD
- Automatic switch-ON by reverse gear or direction lights
- Auto Scanning function
- Automatic Brightness Sensor (Day&Night)
- Distance indication to an obstacle
- Built-in OSD function
- Built-in Speaker
- Temp. -20 ~ 60°C

Specifications

Power input	10V~30V DC, 10 Watt max
Audio/Video input	4-pin mini DIN, 2 channel
Video System	NTSC, PAL
Synchronization	Internal
LCD panel size	5" diagonal
Field of view	Top: 35°, Bottom: 15°, Left: 55°, Right: 55°
Resolution	960(W) x 234(H)
Color configuration	R.G.B. strip
Auto Contrast / Brightness	Built-in day & night sensor
O.S.D. control	Brightness, Contrast, Colour, Image select CA1/CA2 (Normal/Mirror), Auto Scan, Auto Scan Time, Tint (NTSC Only), Distance indication
Speaker	Approx. 35mm, 0.2 Watt max.
Vibration	5.5G
Ambient condition	Indoor use only
Operating temp.	-10°C ~ 50°C
Dimensions	170(W) x 115(H) x 29(D) mm
Weight	Approx. 1.0Kgs